



Two years of fiscal performance by the liquid 5 path Krohne Altosonic-V ultrasonic meter at the Vigdis/Snorre Crossover oil measurement station

Maron J. Dahlstrøm, Saga Petroleum ASA

Two years of fiscal performance

by the liquid 5 path Krohne Altosonic-V ultrasonic meter
at the Vigdis/Snorre Crossover oil measurement station

NSFMW -99

Paper 5


25-28 October 1999

Maron J. Dahlström



Saga Petroleum ASA

Snorre/Vigdis oil process outline



Saga Petroleum ASA


Use liquid ultrasonic meter correctly ! ³

- The ultrasonic liquid meter can output a flow modulated frequency similar to the turbine meter. But, the USM can not be calibrated the same way as a turbine meter : Long time and large volume is required to establish Meter Factor or K-factor. Used directly with a regular prover, hundreds of trials are required for stochastic methods. We now use 1 hour synchronized pulse count.
- In-situ calibration connection ; 4 " 90 degree T 10 D upstream of USM Master resulted in +/- 7% variation in reading, at constant flow. USM need natural profile.
- Master meter installed 10 D after 90 degree bend resulted in some swirl and unwanted offset in flow !

Saga Petroleum ASA



Ultrasonic liquid meter basic nonlinearity ⁴

Never activate Reynolds number compensation, with Reynolds number calculated from entered faulty viscosity ! This mistake resulted in approximate 1 % offset. Note that Snorre/Vigdis Crossover operates in the almost constant effect region.




Typical error compensation curve, with significant error compensation in lower Reynolds number region

Saga Petroleum ASA



Duty ultrasonic meter calibrated with Master ultrasonic meter 1998



*Flowrate approx. 216 to 260 m³/hr; difference + 0,19 % from original
K-factor (4326,9) Hourly repeats inside 0.03 % band*

Saga Petroleum ASA

Improvements in 1998


- The swirl measurement for the Master ultrasonic meter showed more swirl than expected. Krohne therefore activated a swirl effect compensation, based on the swirl factor measurement. This improved the uncertainty, however with some consequences for repeatability.
- Based on the NMI certificate, Krohne removed the meter material temperature compensation.
- Verification was carried out with Master turbine meter as in the previous tests.

Saga Petroleum ASA

New results after swirl compensation 1998

9

Duty ultrasonic calibrated with Master turbine meter



Flowrate approx. 130 m³/hour; difference -0,06 %

Flowrate approx. 270 m³/hour; difference +0,04 %


Flowrate approx. 200 m³/hour; difference +0,09 %

Saga Petroleum ASA

New results after swirl compensation 1998

10

Duty ultrasonic meter calibrated with Master ultrasonic meter



Flowrate approx. 130 m³/hour; difference -0,03 %

Flowrate approx. 170 m³/hour; difference +0,01 %

Flowrate approx. 200 m³/hour; difference -0,07 %

Saga Petroleum ASA

Master turbine meter verification 1998

11


- Examination of the possible bias for the Faure Herman helical rotor turbine meter (linearity $\pm 0.01\%$) from change in flow profile, indicates that this shift normally will be less than 0.2 % .
- Since the K-factor curve for the master turbine meter with upstream section and flow conditioner, still can shift in a new location, the master turbine meter was therefore verified in-situ.

Saga Petroleum ASA

Crossover Metering calibration 1998

12

Compact Prover downstream USM and with turbine meter afterwards



Saga Petroleum ASA

In-Situ calibration performed with Compact Prover & Master turbine meter 1998

13


- Con-Tech Compact Prover with downstream master turbine meter temporarily installed with flexihoses between the master turbine meter run connections.
- Master and Duty ultrasonic meter was calibrated with the master turbine meter. Both ultrasonic meters showed a shift in K-factor curve. The master meter position for this purpose is therefore questioned.
- 1999 performance still show all results for the Duty meter inside 0,10 % from the calibration. All results for Duty meter K-factor is well inside 0,10 % from previous K-factor.

Saga Petroleum ASA

1999 performance

14

Duty ultrasonic meter calibrated with Master ultrasonic meter




All Duty USM K-factors inside +/- 0,10 from 1998 calibration average

Saga Petroleum ASA

Performance

15

Duty ultrasonic meter calibrated with Master ultrasonic meter



All Duty USM K-factors inside ± 0.10 from previous K-factor



Saga Petroleum ASA

In-Situ calibration to be performed with Compact Prover & master turbine meter run 1999


16

- A turbine meter run is calibrated at the Snorre export oil metering station and moved to the position downstream of the Master USM. This turbine will then be in-situ calibrated with the Con-Tech Compact Prover, temporarily installed between the master turbine meter and the return connection.
- Synchronized pulse count for the Master ultrasonic meter and the master turbine meter over one hour will be repeated for each flow point, while the average turbine meter K-factor is determined with the Compact Prover.

Saga Petroleum ASA



Snorre B configuration : Fiscal measurement station for oil with USM



Saga Petroleum ASA

Snorre B calibration philosophy

- The Faure Herman master turbine meter will be calibrated in-situ with regular intervals (initially every 2nd month with Compact Prover temporarily installed into the fixed piping arrangement. The master turbine meter K-factor curve is entered into the Snorre B calibration flowcomputer
- Duty ultrasonic meter is calibrated with the master turbine meter, while verified with the Compact Prover, in a synchronized count of pulses over longer time. Duty USM K-factor curve is entered into the Duty flowcomputer.

Saga Petroleum ASA

Snorre B calibration philosophy

21

- In the operational period between Compact Prover calibration, the Duty USM meter factor will be verified with the turbine meter in a synchronized count of pulses.
- We are considering to use the Duty USM meter factor determination for Compact Prover calibration period alert only, since data indicates that the USM is more reliable than a turbine meter !

Saga Petroleum ASA