

# Halten Øst subsea metering challenges

NFOGM fagdag 29.03.2022

# Halten Øst-Sør concept 2017-2019

- Several licenses involved: PL312, PL312B, PL473 and PL074
- Subsea tie-in to SCMS/Åsgard Compression
  - Flyndretind
  - Gamma
  - Harepus
  - Future tie-in


## Allocation metering concept

- Well MPFMs
- No possibility to test MPFMs against topside metering
- 2 MPFM in series for verification/back-up
- Concept was matured to DG2 status in 2019



# From relinquishment candidate to robust business case

License	Discovery/prospect name	Historical project names/scope		Proposed cluster
PL312	Gamma	Mikkel Sør	Halten Øst-Sør/ «HØS» (DG2 Jan '19, «On hold»)	Halten Øst (DG2 Feb '21)
	Harepus			
	Klatremus (prospect)			
PL473	Flyndretind	Flyndretind		
	Flyndretind Ile (prospect)			
PL263	Sigrid	Sigrid/Natalia (DGO Sept '19)		
	Natalia			
	Rita (prospect)			
PLO74	Nona	Nona/Tussen (DGO Sept '19)		
	Tussen (prospect)			




# The new Halten Øst current concept

Development expanded to six discoveries and 2 production phases:

- Common development of several licenses
- Halten Øst Nord
- Halten Øst Sør
- 6 wells in 2025 + a side-track in 2029 + three optional wells
- Production max: 12 MSm3d

## Subsea facilities:

- 5 x two slot satellites
- 6 production wells – retrievable FCM with MPFMs on each well
- Metering station/PLEM including 2 x MPFM in retrievable modules for allocation metering
- 2 pipelines connecting Nord and Sør satellites to PLEM
- Tie-in spools between PLEM and Midgard pipelines and Åsgard Compression



## NPD “Metering regulations” - Section 13


Multiphase measurement Multiphase measurement may be used if traditional single-phase measurement of hydrocarbons is not possible for financial reasons. The multiphase meter can then be used as a fiscal meter.

### Halten Øst

Subsea MPFMs will be used for allocation metering.

Question: How to comply with NPD regulations regarding:

- Possibility to calibrate meters against test separator or other reference.
- The planned method and interval for sampling and updating PVT data shall be described.



## Halten Øst subsea facilities

# Metering concept

The concept includes three measurement levels:


1. Well MPFMs – for well monitoring and surveillance + back up to allocation meters
2. Metering station MPFMs – Halten Øst field allocation meters
3. Åsgard B Midgard separator metering and sampling
  - a) In normal operation, the two separator trains are shared by Midgard, Mikkell, Åsgard A (gas) and Halten Øst
  - b) In «Halten Øst calibration mode» one train shall be lined up and used as reference metering for testing of Halten Øst subsea MPFMs.
  - c) In «Halten Øst calibration mode», provide Halten Øst fluid sampling at discharge of 1st and 2nd stage separators.

## MPFM performance monitoring


- Continuous monitoring of mass balance between well metering and metering station
- Use subsea meters to pipeline leakage monitoring

# HALTEN ØST – initial PLEM concept 2020

Without metering







Metering station proposal  
concept with 4 MPFMs


Proposed piping arrangement  
From TFMC

## Metering station – example

Unique solution


- Use retrievable FCM concept
- Retrievable choke valve
- Electrically operated isolation valves
- Instrumentation

Footprint: 17 x 10 meter  
220 mT




# PLEM - Metering station

In normal mode the inlet cross-over on the PLEM is closed and south and north productions are measured separately.




## PLEM- metering station

In some production cases, the inlet cross-over needs to be open to avoid extreme velocity in one of the multiphase meters and in these cases the meters need to operate in parallel mode.




# Halten Øst -topside modifications Ågard B

Flow diagram



# «Åsgard allokering»



★ Ikke måling, beregnes

★ Målere installeres i 2022.


★ MPFM process  
Åsgard Compr.

★ Test separator; ikke fiskal.

# Halten Øst PVT handling


## Well meters

Well PVT - initial samples  
- Pres input  
- PVTsim calc.



## Allocation meters


PLEM mixed PVT calculated using:  
- Well PVT  
- Well rates  
- Separate PVT nord/sør



«Calibration mode»


## Reference meters Åsgard B

Sep PVT input  
- density meters  
- PVT sampling / PLEM mix PVT





# Metering - simplified topology Halten Øst scope





# Q & A

# Halten Øst subsea metering challenges

Tore Bratten, EPN OTE POC FISCAL

© Equinor ASA

This presentation, including the contents and arrangement of the contents of each individual page or the collection of the pages, is owned by Equinor. Copyright to all material including, but not limited to, written material, photographs, drawings, images, tables and data remains the property of Equinor. All rights reserved. Any other use, reproduction, translation, adaption, arrangement, alteration, distribution or storage of this presentation, in whole or in part, without the prior written permission of Equinor is prohibited. The information contained in this presentation may not be accurate, up to date or applicable to the circumstances of any particular case, despite our efforts. Equinor cannot accept any liability for any inaccuracies or omissions.